

TB842

System 800xA hardware selector



TB842 ModuleBus Optical Port is a communication interface between the CI801 or CI840/CI840A FCI and the TB820/TB820V2/TB840/TB840A ModuleBus Modem of an I/O cluster or ABB drives units via the Optical ModuleBus. TB842 connects to CI801 via TB806 and to CI840/CI840A via TU847 and TB806 for single I/O or via TU846 and TB846 for redundant I/O.

TB842 can be used in both a simplex optical configuration as well as in a duplex optical configuration. In a simplex configuration, the optical ModuleBus nodes are connected in a ring. In a duplex configuration, the optical ModuleBus nodes are connected in a row. TB842 has a connector for fiber optic connections and a connection to the communication interface module.

The module is equipped with Transmitter/Receiver for up to 10 Mbit/s. Both plastic and HCS (Hard Clad Silica) optic fiber with connectors (Agilent's, former Hewlett-Packard, Versatile Link) can be used with the TB842.

Features and benefits

- 1 fiber optic port for the Optical ModuleBus expansion
- Connection to CI801 and CI840/CI840A

More info

Opto Cable for TB842 according to HP.

Plastic Optical Fiber (POF) (TK811V... or TK812V...) up to 15 meters.

- Extra low loss attenuation
- Simplex or duplex cable
- Latching simplex or duplex connector.
- Cable attenuation maximum 4 dB Hard Clad Silica (HCS) fiber up to 200 meters.
- Riser or plenum
- Simplex or duplex cable
- Latching simplex or duplex connector
- Cable attenuation maximum 2 dB

General info

Protocol	ABB's Modulebus
Article number	3BSE022464R1
Master or slave	Slave
Line redundancy	Yes
Module redundancy	Yes
Hot Swap	Yes
Used together with HI Controller	No
Mounting	Vertical or Horizontal

Detailed data

Connector	Agilent's, former Hewlett-Packard, Versatile Link
24 V consumption typ.	20 mA
ModuleBus current distribution	Fiber optic interface, one transmit and one receive connection for max. 10 Mbit/s. Wavelength 650 nm
Power dissipation	0.5 W

Environmental and certification

Temperature, Operating	55° C (131° F)
Temperature, Storage	-25° C to +70° C
Equipment class	Class I according to IEC 60536; (earth protected)
Ingress protection	IP20 according to IEC 60529
CE- marking	Yes
Electrical Safety	cULus El. safety
Hazardous location	cULus Hazardous Location Class1 Zone 2, ATEX Zone 2
Marine certificates	ABS, BV, DNV-GL, LR, RS, CCS
RoHS compliance	EN 50581:2012
WEEE compliance	DIRECTIVE/2012/19/EU

Dimensions

Height	56.7 mm (2.23")
Width	17.6 mm (0.69")
Depth	42.3 mm (1.67")
Weight (including base)	40 g (0.088 lbs.)

www.abb.com/800xA
www.abb.com/controlsystems

800xA is a registered or pending trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2018 ABB All rights reserved